

# 15-721

## DATABASE SYSTEMS



## Lecture #22 – Larger-than-Memory Databases

---

Andy Pavlo // Carnegie Mellon University // Spring 2016

# ADMINISTRIVIA

---

## **Final Exam: April 27<sup>th</sup> @ 12:00pm**

- Three short-essay questions.
- I will provide sample questions this week.

## **“Final” Presentations: May 6<sup>th</sup> @ 1:00pm**

- 10 minutes per group
- Food and prizes for everyone!

## **Code Reviews: May 8<sup>th</sup> @ 11:59pm**

- I will announce group assignments and guidelines next class.

# QUICKSTEP

---

Pivotal has submitted QuickStep to be an Apache Project.  
They are also working on a distributed version of the system.

<https://wiki.apache.org/incubator/QuickstepProposal>

# TODAY'S AGENDA

---

Background

Implementation Issues

Real-world Examples

Evaluation

# MOTIVATION

---

DRAM is expensive, son.

It would be nice if our in-memory DBMS could use cheaper storage.

# LARGER-THAN-MEMORY DATABASES

---

Allow an in-memory DBMS to store/access data on disk without bringing back all the slow parts of a disk-oriented DBMS.

Need to be aware of hardware access methods

→ In-memory Storage = Tuple-Oriented

→ Disk Storage = Block-Oriented

# OLAP


---

OLAP queries generally access the entire table. Thus, there isn't anything about the workload for the DBMS to exploit that a disk-oriented buffer pool can't handle.

# OLAP

---


OLAP queries generally access the entire table. Thus, there isn't anything about the workload for the DBMS to exploit that a disk-oriented buffer pool can't handle.





# OLAP

OLAP queries generally access the entire table. Thus, there isn't anything about the workload for the DBMS to exploit that a disk-oriented buffer pool can't handle.



# OLTP

---


OLTP workloads almost always have hot and cold portions of the database.

→ We can assume that txns will almost always access hot tuples.


The DBMS needs a mechanism to move cold data out to disk and then retrieve it if it is ever needed again.

# LARGER-THAN-MEMORY DATABASES

*In-Memory  
Index*



*In-Memory  
Table Heap*




*Cold-Data  
Storage*




# LARGER-THAN-MEMORY DATABASES

## *In-Memory Index*




## *In-Memory Table Heap*




## *Cold-Data Storage*




# LARGER-THAN-MEMORY DATABASES




# LARGER-THAN-MEMORY DATABASES



# LARGER-THAN-MEMORY DATABASES




# LARGER-THAN-MEMORY DATABASES






# LARGER-THAN-MEMORY DATABASES

## In-Memory Index




```
SELECT * FROM table
WHERE id = <Tuple #01>
```

## In-Memory Table Heap




## Cold-Data Storage




# LARGER-THAN-MEMORY DATABASES

## In-Memory Index




```
SELECT * FROM table
WHERE id = <Tuple #01>
```

## In-Memory Table Heap




## Cold-Data Storage




# LARGER-THAN-MEMORY DATABASES

## In-Memory Index




```
SELECT * FROM table
WHERE id = <Tuple #01>
```

## In-Memory Table Heap




## Cold-Data Storage




# LARGER-THAN-MEMORY DATABASES

## In-Memory Index



```
SELECT * FROM table
WHERE id = <Tuple #01>
```


## In-Memory Table Heap



???




## Cold-Data Storage



# LARGER-THAN-MEMORY DATABASES

## In-Memory Index




???

```
SELECT * FROM table
WHERE id = <Tuple #01>
```

???


## In-Memory Table Heap



???



## Cold-Data Storage



Evicted Tuple Block

# OLTP ISSUES

---

## **Run-time Operations**

→ Cold Tuple Identification

## **Eviction Policies**

→ Timing

→ Evicted Tuple Metadata

## **Data Retrieval Policies**

→ Granularity

→ Retrieval Mechanism

→ Merging back to memory

# COLD TUPLE IDENTIFICATION

---

## **Choice #1: On-line**

- The DBMS monitors txn access patterns and tracks how often tuples are used.
- Embed the tracking meta-data directly in tuples.

## **Choice #2: Off-line**

- Maintain a tuple access log during txn execution.
- Process in background to compute frequencies.

# EVICTIION TIMING

---

## **Choice #1: Threshold**

- The DBMS monitors memory usage and begins evicting tuples when it reaches a threshold.
- The DBMS has to manually move data.

## **Choice #2: OS Virtual Memory**

- The OS decides when it wants to move data out to disk. This is done in the background.



# EVICTED TUPLE METADATA

---

## Choice #1: Tombstones

- Leave a marker that points to the on-disk tuple.
- Update indexes to point to the tombstone tuples.

## Choice #2: Bloom Filters


- Use approximate data structure for each index.
- Check both index + filter for each query.

## Choice #3: OS Virtual Memory


- The OS tracks what data is on disk. The DBMS does not need to maintain any additional metadata.

# EVICTED TUPLE METADATA


*In-Memory  
Index*



*In-Memory  
Table Heap*




*Cold-Data  
Storage*




# EVICTED TUPLE METADATA


## In-Memory Index




## Access Frequency



## In-Memory Table Heap




## Cold-Data Storage




# EVICTED TUPLE METADATA


## In-Memory Index




## Access Frequency




## In-Memory Table Heap




## Cold-Data Storage




# EVICTED TUPLE METADATA




# EVICTED TUPLE METADATA



# EVICTED TUPLE METADATA




# EVICTED TUPLE METADATA





# EVICTED TUPLE METADATA


*In-Memory  
Index*




*Bloom Filter*



*In-Memory  
Table Heap*



*Cold-Data  
Storage*



# DATA RETRIEVAL GRANULARITY

---

## **Choice #1: Only Tuples Needed**

- Only merge the tuples that were accessed by a query back into the in-memory table heap.
- Requires additional bookkeeping to track holes.

## **Choice #2: All Tuples in Block**

- Merge all the tuples retrieved from a block regardless of whether they are needed.
- More CPU overhead to update indexes.
- Tuples are likely to be evicted again.

# RETRIEVAL MECHANISM

---

## **Choice #1: Abort-and-Restart**

- Abort the txn that accessed the evicted tuple.
- Retrieve the data from disk and merge it into memory with a separate background thread.
- Restart the txn when the data is ready.
- Cannot guarantee consistency for large queries.

## **Choice #2: Synchronous Retrieval**

- Stall the txn when it accesses an evicted tuple while the DBMS fetches the data and merges it back into memory.

# MERGING THRESHOLD

---

## Choice #1: Always Merge

→ Retrieved tuples are always put into table heap.

## Choice #2: Merge Only on Update

→ Retrieved tuples are only merged into table heap if they are used in an **UPDATE** query.

→ All other tuples are put in a temporary buffer.

## Choice #3: Selective Merge

→ Keep track of how often each block is retrieved.

→ If a block's access frequency is above some threshold, merge it back into the table heap.

# REAL-WORLD IMPLEMENTATIONS

---

H-Store – Anti-Caching

Hekaton – Project Siberia

EPFL's VoltDB Prototype

Apache Geode – Overflow Tables

MemSQL – Columnar Tables

# H-STORE – ANTI-CACHING

---

On-line Identification

Administrator-defined Threshold

Tombstones

Abort-and-restart Retrieval

Block-level Granularity

Always Merge



ANTI-CACHING: A NEW APPROACH TO DATABASE  
MANAGEMENT SYSTEM ARCHITECTURE  
*VLDB 2013*

# HEKATON – PROJECT SIBERIA

---

Off-line Identification

Administrator-defined Threshold

Bloom Filters

Synchronous Retrieval

Tuple-level Granularity

Always Merge



TREKKING THROUGH SIBERIA: MANAGING COLD  
DATA IN A MEMORY-OPTIMIZED DATABASE  
*VLDB 2014*

# EPFL VOLTDB

---

Off-line Identification

OS Virtual Memory

Synchronous Retrieval

Page-level Granularity

Always Merge




ENABLING EFFICIENT OS PAGING FOR MAIN-  
MEMORY OLTP DATABASES  
*DAMON 2013*



# EPFL VOLTDB

---


*In-Memory  
Table Heap*




*Cold-Data  
Storage*




# EPFL VOLTDB




# EPFL VOLTDB




# EPFL VOLTDB




# EPFL VOLTDB




# EPFL VOLTDB



# EPFL VOLTDB




# EPFL VOLTDB






# EPFL VOLTDB



# EPFL VOLTDB



# APACHE GEODE – OVERFLOW TABLES

---

On-line Identification

Administrator-defined Threshold

Tombstones (?)

Synchronous Retrieval

Tuple-level Granularity

Merge Only on Update (?)

# MEMSQL – COLUMNAR TABLES

---

Administrator manually declares a table as a distinct disk-resident columnar table.

- Appears as a separate logical table to the application.
- Uses **mmap** to manage buffer pool.
- Pre-computed aggregates per block always in memory.

Manual Identification

No Evicted Metadata is needed.

Synchronous Retrieval

Always Merge

# EVALUATION

---

Compare different design decisions in H-Store with anti-caching.

## Storage Devices:


- Hard-Disk Drive (HDD)
- Shingled Magnetic Recording Drive (SMR)
- Solid-State Drive (SSD)
- 3D XPoint (3DX)
- Non-volatile Memory (NVRAM)



LARGER-THAN-MEMORY DATA MANAGEMENT  
ON MODERN STORAGE HARDWARE FOR IN-  
MEMORY OLTP DATABASE SYSTEMS  
*UNDER SUBMISSION*


# MICROBENCHMARK

*10m Tuples - 1KB each*  
*50% Reads / 50% Writes - Synchronization Enabled*




# MICROBENCHMARK

*10m Tuples - 1KB each*  
*50% Reads / 50% Writes - Synchronization Enabled*



# MICROBENCHMARK


*10m Tuples - 1KB each*  
*50% Reads / 50% Writes - Synchronization Enabled*






# MERGING THRESHOLD

*YCSB Workload – 90% Reads / 10% Writes*  
*10GB Database using 1.25GB Memory*




# MERGING THRESHOLD

*YCSB Workload – 90% Reads / 10% Writes*  
*10GB Database using 1.25GB Memory*



# MERGING THRESHOLD

*YCSB Workload – 90% Reads / 10% Writes*  
*10GB Database using 1.25GB Memory*



# CONFIGURATION COMPARISON

---

## **Generic Configuration**

- Abort-and-Restart Retrieval
- Merge (All) Threshold
- 1024 KB Block Size


## **Optimized Configuration**

- Synchronous Retrieval
- Top-5% Merge Threshold
- Block Sizes (HDD/SMR - 1024 KB) (SSD/3DX - 16 KB)

# TATP BENCHMARK


*Optimal Configuration per Storage Device*  
*1.25GB Memory*

■ Generic      ■ Optimized



# VOTER BENCHMARK

*Optimal Configuration per Storage Device*  
*1.25GB Memory*



# PARTING THOUGHTS

---

Today was about working around the block-oriented access and slowness of secondary storage.

Fast & cheap byte-addressable NVM will make this lecture unnecessary.

# NEXT CLASS

---

Non-Volatile Memory  
Project #3 Code Reviews